



# PALLMANN®

wood floors. protected

## Translation of the original operating instructions English

Pallmann Pre-Separator

Powerful pre-separator that filters out large amounts of coarse dirt and fine dust before vacuuming.

### Features:

- ▶ Constant suction power
- ▶ Protection of the vacuum cleaner and filter
- ▶ Particle separation rate up to 99%
- ▶ Easy to empty using standard garbage bags
- ▶ Static conductive hose and cyclone
- ▶ Due to the static conductivity, it is particularly suited for wood dust

### Technical Data

Weight . . . . . 22 lbs  
Dimensions . . . . . Ø50x4.92 ft  
Hose length . . . . . 1.5 m  
Filling quantity . . . . . 13.2 gallons

### Included:

- ▶ Completely assembled cyclone
- ▶ Dirt container
- ▶ Hose 4,92 ft, #82202

### Instructions for use:

The pre-separator is assembled between the vacuum cleaner and machine.

It can be used wood flooring and monodisc grinding machines, saws, hand-held sanding machines and many other electrical devices and can also be used for vacuuming surfaces with a floor nozzle.

Hose to the vacuum cleaner #82202 (Included)

Hose to the Machine (Not included)



Make sure that the hose between the machine and the cyclone is always free and open. A clogged hose can lead to extreme underpressure in the dust container and destroy it.

### Operation:

- ▶ Insert the garbage bag in the pail.
- ▶ Close the pail with the clamping ring.
- ▶ Connect the outlet of the pre-separator with the vacuum cleaner.
- ▶ Connect the suction hose of the machine to the inlet on the side of the pre-separator and fasten it to the strain relief.
- ▶ After the work is complete, empty the dust container.

Pallmann recommends the industrial vacuum:  
Pallmann Hepa VAC #085638